



|            |                     |
|------------|---------------------|
| PART NO.   | CONDUCTOR MATERIAL  |
| FA12133    | PLATINUM / RHODIUM* |
| FA12133-02 | CONSTANTAN          |

|              |                  |
|--------------|------------------|
| RATINGS      |                  |
| PRESSURE:    | 3500 PSIG @ 20°C |
| TEMPERATURE: | -269°C TO 450°C  |

\*USES COMPENSATING WIRE  
 MAXIMUM JUNCTION TEMPERATURE 250°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12133SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

SINGLE LEG T/C (-) LOOP STYLE

PART NO. (SEE TABLE) REV. A

|      |       |            |             |                           |           |    |            |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| REV. | APP'D | DATE       | SCALE 1:1   | DIMENSIONS IN INCHES [mm] | DRAWN     | MH | 09/01/2006 |
| A2   | JS    | 05/24/2013 | FTCL0086-ST |                           | ENG APPR. | MH | 09/01/2006 |

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**