



RATINGS	
VOLTAGE:	500 V DC
PRESSURE:	2500 PSIG @ 20°C
TEMPERATURE:	-80°C TO 450°C*

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12231SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FEEDTHROUGH

PART NO. FA12231 REV. A

REV.	APP'D	DATE	SCALE 8:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/29/2006
A2	JS	05/20/2013	FTCL0017-01		ENG APPR.	MH	08/29/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.