



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12278	COPPER	55 AMPS
FA12278-02	MOLYBDENUM	28 AMPS
FA12278-03	NICKEL	16.5 AMPS
FA12278-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12278SL REV. B2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWELVE 5KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. B

REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	JM	12/28/2005
B2	JS	05/20/2013	MPST0012-ST		ENG APPR.	MH	04/28/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.