


PART NO.	COND MATERIAL	W WALL
FA12336	COPPER	.032 [0.81]
FA12336-02	NICKEL 200	.035 [0.89]
FA12336-03	304 STN STL	.035 [.089]

RATINGS	
VOLTAGE:	12KV DC
PRESSURE:	750 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

ONE 12KV FEEDTHROUGH

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12336SL REV. A3

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	5/3/2006
A3	JS	05/20/2013	FTST0001-2ST		ENG APPR.	MH	08/11/2006

PART NO. (SEE TABLE) REV. A

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.