



PART NO.	AIR SIDE PLUG
FA12628	NO
KT12628	YES

RATINGS	
PIN / SHIELD VOLTAGE:	500V DC
SHIELD / GROUND VOLTAGE:	2.5KV DC
CURRENT:	3.6 AMPS
PRESSURE:	300 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-80°C TO 450°C*
TEMPERATURE WITH PLUG:	-65°C TO 165°C

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA12628SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FLOATING SHIELD BNC

PART NO. FA12628 REV. A

REV.	APP'D	DATE	SCALE 3:2	DIMENSIONS IN INCHES [mm]	DRAWN	EB	5/24/2006
A2	JS	09/27/2012	COBN0019-01		ENG APPR.	MH	07/13/2006