



PART NO.	CONDUCTOR MATERIAL	CURRENT	AIR SIDE PLUG
FA12655	NICKEL	16 AMPS	NO
KT12655	NICKEL	16 AMPS	YES
FA12655-02	MOLYBDENUM	23 AMPS	NO
KT12655-02	MOLYBDENUM	23 AMPS	YES

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
VOLTAGE:	700V DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	475 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 125°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: <b>FOUR PIN CONNECTOR</b>		<a href="http://WWW.SOLIDSEALING.COM">WWW.SOLIDSEALING.COM</a> 	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	5/3/2006	PART NO. (SEE TABLE) REV. A		
A2	JS	11/26/2012	MPDP0020-0ST		ENG APPR.	MH	08/14/2006			SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA12655SL REV. A2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**