



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12691	COPPER	55 AMPS
FA12691-02	MOLYBDENUM	28 AMPS
FA12691-03	NICKEL	16.5 AMPS
FA12691-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE EIGHT 5KV FEEDTHROUGHS			
REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	JM	12/28/2005	PART NO. (SEE TABLE) REV. C	WWW.SOLIDSEALING.COM
C1	JF	01/31/2025	MPST0020-1ST		ENG APPR.	MH	04/28/2006		SALES DWG NO. FA12691SL REV. C1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.