


PART NO.	AIR SIDE PLUG
FA12779	NO
KT12779	YES

RATINGS	
VOLTAGE:	500V DC
CURRENT:	0.8 AMPS
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 350°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

DOUBLE ENDED 50 OHM SMA

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	12/28/2005
A2	JS	10/22/2012	COSA0010-01		ENG APPR.	MH	05/15/2006

PART NO. FA12779 REV. A

SALES DWG NO. FA12779SL REV. A2