


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12916	COPPER	330 AMPS
FA12916-02	MOLYBDENUM	165 AMPS
FA12916-03	NICKEL	98 AMPS
FA12916-04	304 STN STL	21 AMPS

RATINGS	
VOLTAGE:	3KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

3 KV FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	JM	4/5/2006
B2	JS	09/24/2012	FTCL0046-0ST		ENG APPR.	MH	08/14/2006

PART NO. (SEE TABLE) REV. B

SALES DWG NO. FA12916SL REV. B2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**