

| PART NO. | REMARKS | CONDUCTOR MATERIAL | CURRENT | VOLTAGE | AIR SIDE PLUG |
|------------|---------|--------------------|----------|---------|---------------|
| FA13080 | POWER | ALL ALUMEL | 4.8 AMPS | 700V DC | NO |
| KT13080 | POWER | ALL ALUMEL | 4.8 AMPS | 700V DC | YES |
| FA13080-02 | T/C | CHROMEL / ALUMEL | N/A | N/A | NO |
| KT13080-02 | T/C | CHROMEL / ALUMEL | N/A | N/A | YES |

| RATINGS | |
|---------------------------|-------------------|
| CONDUCTOR MATERIAL: | SEE TABLE AT LEFT |
| CURRENT: | SEE TABLE AT LEFT |
| VOLTAGE: | SEE TABLE AT LEFT |
| PRESSURE: | 200 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -25°C TO 205°C |
| TEMPERATURE WITH PLUG: | -25°C TO 125°C |

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13080SL REV. C2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TEN PIN BASEPLATE FEEDTHROUGH

PART NO. (SEE TABLE) REV. C

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 12/27/2005 |
|------|-------|------------|--------------|---------------------------|-----------|----|------------|
| C2 | JS | 09/24/2012 | MPDP0021-0ST | | ENG APPR. | MH | 05/26/2006 |