


PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA13091	CHROMEL / ALUMEL	K
FA13091-02	IRON / CONSTANTAN	J
FA13091-03	TUNGSTEN / RHENIUM*	C
FA13091-04	CHROMEL / CONSTANTAN	E

* TYPE C USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
PRESSURE:	800 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-29°C TO 218°C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE:
 TWO PAIR T/C SPADE TYPE

WWW.SOLIDSEALING.COM



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]
A2	JS	06/11/2013	MPLC0031-1ST	

DRAWN	JM	10/25/2005
ENG APPR.	MH	05/22/2006

PART NO. (SEE TABLE) REV. A

SOLID SEALING TECHNOLOGY, INC.
 SALES DWG NO. FA13091SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.