



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA13103	COPPER	30 AMPS	55 AMPS
FA13103-02	MOLYBDENUM	28 AMPS	28 AMPS
FA13103-03	NICKEL	16.5 AMPS	16.5 AMPS
FA13103-04	304 STN STL	3.6 AMPS	3.6 AMPS

	RATINGS	
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	20KV DC	12KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C	1500 PSIG @ 20°C
TEMPERATURE:	-55°C TO 125°C	-269°C TO 450°C

MATES WITH POWERPLUG FP10883 & FP10883-02

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: TWELVE 20KV FEEDTHROUGHS		
REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/29/2006	PART NO. (SEE TABLE) REV. B	
B3	JS	05/20/2013	MPST0047-1ST		ENG APPR.	MH	08/29/2006		

SOLID SEALING TECHNOLOGY, INC.
 SALES DWG NO. FA13103SL REV. B3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.