



PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA13603
 -AIR SIDE PLUG KT14876

RATINGS	
VOLTAGE:	500V DC
CURRENT:	5 AMPS
PRESSURE:	1350 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 9 PIN SUB D CONNECTOR		WWW.SOLIDSEALING.COM 	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	2/15/2006	PART NO. FA13118 REV. C		
C3	JS	11/21/2012	MPCL0059-01		ENG APPR.	MH	08/25/2006			SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA13118SL REV. C3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.