


PART NO.	CONDUCTOR MATERIAL	W WALL
FA13176	COPPER	.032 [0.81]
FA13176-02	304 STN STL	.035 [0.89]

RATINGS	
VOLTAGE:	8KV DC
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

SINGLE 8KV FEEDTHROUGH

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	3/8/2006
A3	JS	05/20/2013	FTCL0013-11		ENG APPR.	MH	08/25/2006

PART NO. FA13176 REV. A

SALES DWG NO. FA13176SL REV. A3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.