



PART NO.	CONDUCTOR MATERIAL
FA13178	ALUMEL
FA13178-02	CONSTANTAN
FA13178-03	TUNGSTEN 26%/ RHENIUM*

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
PRESSURE:	3500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

*USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE SINGLE T/C (-) FEEDTHROUGH				
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	5/3/2006	PART NO. (SEE TABLE) REV. D		WWW.SOLIDSEALING.COM
D1	JF	05/07/2020	FTCL0048-ST		ENG APPR.	MH	08/14/2006			SALES DWG NO. FA13178SL REV. D1

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.