



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13205	COPPER	330 AMPS
FA13205-03	NICKEL	98 AMPS
FA13205-04	304 STN STL	21 AMPS

RATINGS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: <b>2 CONDUCTOR FEEDTHROUGH</b>		<a href="http://WWW.SOLIDSEALING.COM">WWW.SOLIDSEALING.COM</a> 		
REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	MH	02/28/2006	PART NO. (SEE TABLE) REV. A		<b>SOLID SEALING TECHNOLOGY, INC.</b>	
A2	JS	12/16/2013	MPCL0064-0ST		ENG APPR.	MH	02/28/2006			SALES DWG NO. FA13205SL REV. A2	

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**