


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13230	COPPER	185 AMPS
FA13230-02	MOLYBDENUM	93 AMPS
FA13230-03	NICKEL	56 AMPS
FA13230-04	304 STN STL	12 AMPS

RATINGS	
VOTLAGE:	12KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	750 PSIG @ 20°C
TEMPERAURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 12KV FEEDTHROUGHS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 7:8	DIMENSIONS IN INCHES [mm]	DRAWN	JM	12/28/2005
A2	JS	05/20/2013	FTST0031-1ST		ENG APPR.	MH	03/21/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13230SL REV. A2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**