

RATINGS					
CURRENT:	13 AMPS				
VOLTAGE:	12 KV DC				
PRESSURE:	200 PSIG @ 20°C				
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C				
TEMPERATURE WITH PLUG:	-15°C TO 85°C				

WWW.SOLIDSEALING.C	OM

PARI NO. FAI 3340 REV. A										
Sole PROPERTY OF Solid Sealing Technology. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED. Image: Constraint of the sealing technology is prohibited. REV. APP'D DATE SCALE 1:1 DIMENSIONS IN DRAWN DRAWN MH 12/12/2006 PART NO. FA13340 REV. A		PROPRIETARY AND CONFIDENTIAL				THIRD ANGLE PROJECTION			TITLE:	
PARI NO. FAI3340 REV. A		SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN						7 PIN CONNECTOR		
A4 IS 11/26/2012 MPST0017-02 INCHES [mm] ENG APPR MH 12/12/2004 TAKINO, TAT5540 KLV, A SALES DWG NO FA13340SL REV	REV	. APP'D	DATE	SCALE 1:1	DIMENSIONS IN	DRAWN	MH	12/12/2006	PARTNO EA13340 REV A	SOLID SEALING TECHNOLOGY, INC.
	A4	JS	11/26/2012	MPST0017-02	INCHES [mm]	ENG APPR.	MH	12/12/2006	TARTNO, TAT5540 REV.A	SALES DWG NO. FA13340SL REV. A4

AIR SIDE PLUG

NO

YES

PART NO. FA13340

KT13340