

PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA13385	COPPER	30 AMPS	55 AMPS
FA13385-02	MOLYBDENUM	28 AMPS	28 AMPS
FA13385-03	NICKEL	16.5 AMPS	16.5 AMPS
FA13385-04	304 STN STL	3.6 AMPS	3.6 AMPS


	RATINGS	
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	20KV DC	14KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	1500 PSIG @ 20°C	1500 PSIG @ 20°C
TEMPERATURE:	-55°C TO 125°C	-269°C TO 450°C

MATES WITH POWERPLUG FP10883 & FP10883-02

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

THREE 20KV FEEDTHROUGHS



**SOLID SEALING TECHNOLOGY, INC.**

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	EB	5/22/2006
A3	JS	05/20/2013	MPST0045-0ST		ENG APPR.	MH	08/23/2006

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13385SL REV. A3

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**