



PART NO.	AIR SIDE PLUG
FA13393	NO
KT13393	YES

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	10 AMPS
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				
REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]
A2	JS	10/22/2012	COS50006-01	

THIRD ANGLE PROJECTION		
DRAWN	JM	1/25/2006
ENG APPR.	MH	05/15/2006

TITLE:	QUAD 5KV SHV EXPOSED
PART NO. FA13393 REV. A	

WWW.SOLIDSEALING.COM

SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13393SL REV. A2