

PART NO.	AIR SIDE PLUG
FA13401	NO
KT13401	YES


RATINGS			
VOLTAGE:	5KV DC		
CURRENT:	10 AMPS		
PRESSURE:	1600 PSIG @ 20°C		
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C		
TEMPERATURE WITH PLUG:	-65°C TO 165°C		

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]
A2	JS	10/22/2012	COS50010-03	

THIRD ANGLE PROJECTION



IN	DRAWN	JM	2/22/2006		
1]	ENG APPR.	MH	08/25/2006		

TITLE:

5KV RECESSED SHV CONNECTOR

PART NO. FA13401 REV. A



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13401SL REV. A2