


PERFORMANCE SPECIFICATIONS	
VOLTAGE:	8KV DC
CURRENT:	1000 AMPS
PRESSURE:	25-100 PSI @ 20°C
FLOW RATE:	0.3 GPM @ 15°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE
 8KV LIQUID COOLED FEEDTHRU



REV.	APP'D	DATE	SCALE 1:2	DIMENSIONS IN INCHES [mm]	DRAWN	JM	3/22/2006
D2	JF	12/8/2020	FTCL0053-01		ENG APPR.	MH	05/11/2006

PART NO. FA13510 REV. D

WWW.SOLIDSEALING.COM
 SALES DWG NO. FA13510SL REV. D2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.