



|          |               |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA13583  | NO            |
| KT13583  | YES           |

| RATINGS                   |                  |
|---------------------------|------------------|
| VOLTAGE:                  | 1.5KV DC         |
| CURRENT:                  | 3.6 AMPS         |
| PRESSURE:                 | 1800 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C  |
| TEMPERATURE WITH PLUG:    | -65°C TO 165°C   |

|  |       |            |             |                            |           |                               |            |  |  |
|--|-------|------------|-------------|----------------------------|-----------|-------------------------------|------------|--|--|
| PROPRIETARY AND CONFIDENTIAL<br>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED. |       |            |             | THIRD ANGLE PROJECTION<br> |           | TITLE:<br>DOUBLE ENDED TYPE N |            | <a href="http://WWW.SOLIDSEALING.COM">WWW.SOLIDSEALING.COM</a><br> |  |
| REV.   | APP'D | DATE       | SCALE 2:1   | DIMENSIONS IN INCHES [mm]  | DRAWN     | JS                            | 6/16/2008  | PART NO. FA13583 REV. B<br>SALES DWG NO. FA13583SL REV. B2         |  |
| B2   | JS    | 10/19/2012 | COTN0007-01 |                            | ENG APPR. | MH                            | 07/08/2008 |  |  |