



| PART NO. | AIR SIDE PLUG |
|----------|---------------|
| FA13608  | NO            |
| KT13608  | YES           |

| PERFORMANCE SPECIFICATIONS |                  |
|----------------------------|------------------|
| VOLTAGE:                   | 500V DC          |
| CURRENT:                   | 3.6 AMPS         |
| PRESSURE:                  | 1400 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG:  | -269°C TO 450°C  |
| TEMPERATURE WITH PLUG:     | -65°C TO 165°C   |

|  |       |            |             |                            |           |  |            |                         |  |                                 |  |
|--|-------|------------|-------------|----------------------------|-----------|--|------------|-------------------------|--|---------------------------------|--|
| PROPRIETARY AND CONFIDENTIAL<br>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED. |       |            |             | THIRD ANGLE PROJECTION<br> |           | TITLE<br><b>DOUBLE ENDED BNC CONNECTOR</b> |            |                         |  |                                 |  |
| REV.   | APP'D | DATE       | SCALE 2.5:1 | DIMENSIONS IN INCHES [mm]  | DRAWN     | JM   | 1/18/2006  | PART NO. FA13608 REV. F |  | WWW.SOLIDSEALING.COM            |  |
| F1   | JF    | 03/12/2024 | COBN0027-11 |                            | ENG APPR. | MH   | 05/15/2006 |                         |  | SALES DWG NO. FA13608SL REV. F1 |  |

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**