



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13792	COPPER	55 AMPS
FA13792-02	MOLYBDENUM	28 AMPS
FA13792-03	NICKEL	16.5 AMPS
FA13792-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	2KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.					THIRD ANGLE PROJECTION 			TITLE: 2KV BASEPLATE FEEDTHROUGH		WWW.SOLIDSEALING.COM 	
REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	JM	2/22/2006	PART NO. (SEE TABLE) REV. C		SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA13792SL REV. C4	
C4	JS	09/24/2012	MPST0027-0ST		ENG APPR.	MH	06/06/2006				

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.