



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13793	COPPER	55 AMPS
FA13793-02	MOLYBDENUM	28 AMPS
FA13793-03	NICKEL	16.5 AMPS
FA13793-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	2 KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 2 KV BASEPLATE FEEDTHROUGH		WWW.SOLIDSEALING.COM SOLID SEALING TECHNOLOGY, INC.
REV. C2 APP'D JS DATE 09/26/2012 SCALE 3:4 DIMENSIONS IN INCHES [mm]	DRAWN JS ENG APPR. MH DATE 3/21/2008 DATE 06/16/2008	PART NO. (SEE TABLE) REV. C		SALES DWG NO. FA13793SL REV. C2					

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.