

RATINGS	
CONDUCTOR MATERIAL:	COPPER
VOLTAGE:	12KV DC
CURRENT:	185 AMPS
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13804SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

12KV BASEPLATE FEEDTHROUGH

PART NO. FA13804 REV. A

REV.	APP'D	DATE	SCALE 1:1.14286	DIMENSIONS IN INCHES [mm]	DRAWN	EB	5/24/2006
A2	JS	09/24/2012	FTCL0056-01		ENG APPR.	MH	08/23/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.