


PART NO.	CONDUCTOR MATERIAL	CURRENT
FA13806	COPPER	55 AMPS
FA13806-02	MOLYBDENUM	28 AMPS
FA13806-03	NICKEL	16.5 AMPS
FA13806-04	304 STN STL	3.6 AMPS

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE:	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

5KV FEEDTHRU

WWW.SOLIDSEALING.COM

SST

SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	JS	6/20/2007
A2	JS	09/24/2012	FTST0068-1ST		ENG APPR.	MH	06/10/2008

PART NO. (SEE TABLE) REV. A

SALES DWG NO. FA13806SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.