

PLUGS SOLD SEPARATELY:  
 - AIR SIDE W/SOLDER CONTACTS FP14900  
 - AIR SIDE W/CRIMP CONTACTS KT14378

RATINGS	
VOLTAGE:	1 KV DC
CURRENT:	5 AMPS
PRESSURE:	450 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA13807SL REV. A3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

10 PIN CONNECTOR

PART NO. FA13807 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	04/13/2006
A3	JS	11/26/2012	MPCL0106-01SL		ENG APPR.	MH	04/17/2006

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**