



PLUGS SOLD SEPARATELY:
 - AIR SIDE W/SOLDER CONTACTS FP14901
 - AIR SIDE W/CRIMP CONTACTS KT14379

RATINGS	
VOLTAGE:	1 KV DC
CURRENT:	3 AMPS
PRESSURE:	400 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA13808SL REV. A3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

19 PIN CONNECTOR

PART NO. FA13808 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	03/29/2006
A3	JS	11/26/2012	MPCL0102-01SL		ENG APPR.	MH	04/06/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.