


RATINGS	
CONDUCTOR MATERIAL	COPPER
VOLTAGE	12KV DC
CURRENT	185 AMPS
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE	-25°C TO 205°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

BASEPLATE FEEDTHRU

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 3:4	DIMENSIONS IN INCHES [mm]	DRAWN	MH	03/13/2007
A3	JS	09/24/2012	FTCL0062-01		ENG APPR.	MH	03/13/2007

PART NO. FA13818 REV. A

SALES DWG NO. FA13818SL REV. A3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.