



PERFORMANCE SPECIFICATIONS	
VOLTAGE:	8KV DC
CURRENT:	1000 AMPS
PRESSURE:	25-100 PSI @ 20°C
FLOW RATE:	0.3 GPM @ 15°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 8KV LIQUID COOLED FEEDTHRU					
REV.	APP'D	DATE	SCALE 1:2	DIMENSIONS IN INCHES [mm]	DRAWN	JM	3/1/2006	PART NO. FA14050 REV. B		WWW.SOLIDSEALING.COM	
B3	JF	12/8/2020	FTCL0069-01		ENG APPR.	MH	08/25/2006			SALES DWG NO. FA14050SL REV. B3	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.