



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA14056	COPPER	16 AMPS
FA14056-02	MOLYBDENUM	8.5 AMPS
FA14056-03	NICKEL	5 AMPS
FA14056-04	304 STN STL	1.1 AMPS

RATINGS	
VOLTAGE:	2 KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	1400 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14056SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR 2KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 5:4	DIMENSIONS IN INCHES [mm]	DRAWN	JF	07/15/2014
A1	JF	07/15/2014	MPDC0013-0ST		ENG APPR.	JF	07/15/2014

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.