



PART NO.	AIR SIDE PLUG
FA14091	NO
KT14091	YES

RATINGS	
VOLTAGE:	1.5KV DC
CURRENT:	5 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C
TEMPERATURE WITH PLUG:	-25°C TO 165°C

\*FOR INTERNAL PRESSURE 5 TO 100 PSIG  
AN OVERPRESSURE RING IS REQUIRED.

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)

<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.</div>					<div>THIRD ANGLE PROJECTION</div> <div></div>			<div>TITLE:</div> <div>50 OHM TYPE N CONNECTOR</div>		<div></div> <div><b>SOLID SEALING TECHNOLOGY, INC.</b></div>	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	09/14/2006	PART NO. FA14091 REV. A		SALES DWG NO. FA14091SL REV. A2	
A2	JS	10/19/2012	COTN0011-11		ENG APPR.	MH	10/19/2012				

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**