

PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUGS	CURRENT WITHOUT PLUGS
FA14234	COPPER	30 AMPS	55 AMPS
FA14234-02	MOLYBDENUM	28 AMPS	28 AMPS
FA14234-03	NICKEL	16.5 AMPS	16.5 AMPS
FA14234-04	304 STN STL	3.6 AMPS	3.6 AMPS

	RATINGS	
	WITH PLUG	WITHOUT PLUG
VOTLAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 125°C	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG
AN OVERPRESSURE RING IS REQUIRED.

MATES WITH POWERPLUG FP10884 & FP10884-02

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14234SL REV. B3

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

EIGHT 10KV FEEDTHROUGHS

PART NO. (SEE TABLE) REV. B

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	3/1/2006
B3	JS	05/21/2013	MPST0043-1ST		ENG APPR.	MH	08/25/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.