

| | |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA14292 | NO |
| KT14292 | YES |

| RATINGS | |
|---------------------------|------------------|
| VOLTAGE: | 5 KV DC |
| CURRENT: | 10 AMPS |
| PRESSURE: | 1500 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C |
| TEMPERATURE WITH PLUG: | -65°C TO 165°C |

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14292SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

TWO 5KV SHV CONNECTORS

PART NO. FA14292 REV. A

| REV. | APP'D | DATE | SCALE 1:1 | DIMENSIONS IN INCHES [mm] | DRAWN | JM | 3/14/2006 |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| A2 | JS | 10/22/2012 | COSS0017-01 | | ENG APPR. | MH | 04/24/2006 |