

PART NO.	AIR SIDE PLUG
FA14319	NO
KT14319	YES

RATINGS	
VOLTAGE:	500V DC
CURRENT:	1.8 AMPS
PRESSURE:	3000 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14319SL REV. B1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

SMA CONNECTOR

PART NO. FA14319 REV. B

REV.	APP'D	DATE	SCALE 2.5:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	3/14/2006
B1	JF	12/23/2013	COSA0014-16		ENG APPR.	MH	06/06/2006