


PLUGS SOLD SEPARATELY:  
 -VACUUM SIDE PEEK PLUG FA13604  
 -AIR SIDE PLUG KT14877

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	500V DC
CURRENT:	5 AMPS
PRESSURE:	1250 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE  
 (2) 15 PIN SUB D CONNECTORS



REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	JS	03/26/2010
B1	CW	4/13/2022	MPCL0090-01		ENG APPR.	JS	03/26/2010

PART NO. FA14341 REV. B

WWW.SOLIDSEALING.COM  
 SALES DWG NO. FA14341SL REV. B1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**