


|          |               |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA14391  | NO            |
| KT14391  | YES           |

| PERFORMANCE SPECIFICATIONS |                 |
|----------------------------|-----------------|
| VOLTAGE:                   | 12 KV DC        |
| CURRENT:                   | 13 AMPS         |
| TEMPERATURE WITHOUT PLUG:  | -269°C TO 450°C |
| TEMPERATURE WITH PLUG:     | -15°C TO 85°C   |

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE  
**4 PIN CONNECTOR**



|      |       |            |             |                           |           |    |            |
|------|-------|------------|-------------|---------------------------|-----------|----|------------|
| REV. | APP'D | DATE       | SCALE 1:1   | DIMENSIONS IN INCHES [mm] | DRAWN     | JS | 04/06/2012 |
| A2   | JF    | 06/23/2021 | MPST0070-12 |                           | ENG APPR. | JS | 04/06/2012 |

PART NO. FA14391 REV. A

WWW.SOLIDSEALING.COM  
 SALES DWG NO. FA14391SL REV. A2

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**