



PART NO	AIR SIDE PLUG
FA14392	NO
KT14392	YES

RATINGS	
VOLTAGE:	12 KV DC
CURRENT:	13 AMPS
PRESSURE:	200 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-15°C TO 85°C

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14392SL REV. B1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

7 PIN CONNECTOR

PART NO. FA14392 REV. B

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	03/26/2008
B1	JS	11/26/2012	MPST0071-11		ENG APPR.	MH	03/26/2008