



PART NO.	AIR SIDE PLUG
FA14539	NO
KT14539	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	7KV DC
CURRENT:	7 AMPS
PRESSURE:	320 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 150°C*
TEMPERATURE WITH PLUG:	-55°C TO 150°C

\*200°C SHORT TERM, 150°C CONTINUOUS

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE <b>HN CONNECTOR</b>			
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	06/26/2006	<b>PART NO. FA14539 REV. A</b>	<a href="http://WWW.SOLIDSEALING.COM">WWW.SOLIDSEALING.COM</a>
A4	MH	1/20/2021	COHN001-01		ENG APPR.	MH	06/27/2006		SALES DWG NO. FA14539SL REV. A4

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**