



PART NO.	AIR SIDE PLUG
FA14539	NO
KT14539	YES

PERFORMANCE SPECIFICATIONS	
VOLTAGE (DWV):	7KV DC
OPERATING VOLTAGE:	1.5KV DC*
CURRENT:	7 AMPS
PRESSURE:	320 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 150°C**
TEMPERATURE WITH PLUG:	-65°C TO 150°C

*BASED ON AIR SIDE PLUG

**200°C SHORT TERM, 150°C CONTINUOUS

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				 THIRD ANGLE PROJECTION		TITLE HN CONNECTOR				
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	06/26/2006	PART NO. FA14539 REV. A	WWW.SOLIDSEALING.COM	
A5	JF	02/24/2025	COHN0001-01		ENG APPR.	MH	06/27/2006		SALES DWG NO. FA14539SL REV. A5	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.