

PART NO.	AIR SIDE PLUG
FA14574	NO
KT14574	YES

RATINGS				
VOLTAGE:	500V DC			
CURRENT:	3.6 AMPS			
PRESSURE:	0 PSIG @ 20°C*			
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C			
TEMPERATURE WITH PLUG:	-25°C TO 165°C			


\*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN
A2	JS	10/15/2012	COBN0025-03	INCHES [mm]

## THIRD ANGLE PROJECTION



	•			
N	DRAWN	MH	09/18/2006	
]	ENG APPR.	MH	10/27/2006	

## TITLE:

DOUBLE ENDED BNC CONNECTOR

PART NO. FA14574 REV. A



WWW.SOLIDSEALING.COM

SALES DWG NO. FA14574SL REV. A2