

PART NO.	AIR SIDE PLUG
FA14576	NO
KT14576	YES

RATINGS				
VOLTAGE:	500V DC			
CURRENT:	3.6 AMPS			
PRESSURE:	0 PSIG @ 20°C*			
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C			
TEMPERATURE WITH PLUG:	-25°C TO 165°C			


*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

REV.	APP'D	DATE	SCALE 1.5:1	DIMENSIONS IN INCHES [mm]
A2	JS	10/04/2012	COBN0014-03	

THIRD ANGLE PROJECTION



Ν	DRAWN	MH	09/18/2006
	ENG APPR.	МН	10/27/2006

TITLE:

BNC CONNECTOR

PART NO. FA14576 REV. A





OLID SEALING TECHNOLOGI, IN

SALES DWG NO. FA14576SL REV. A2