



| | |
|----------|---------------|
| PART NO. | AIR SIDE PLUG |
| FA14760 | NO |
| KT14760 | YES |

| RATINGS | |
|---------------------------|-----------------|
| PIN / SHIELD VOLTAGE: | 500V DC |
| SHIELD / GROUND VOLTAGE: | 2.5KV DC |
| CURRENT: | 3.6 AMPS |
| PRESSURE: | 300 PSIG @ 20°C |
| TEMPERATURE WITHOUT PLUG: | -80°C TO 450°C* |
| TEMPERATURE WITH PLUG: | -65°C TO 165°C |

* CALL SST TO CONFIRM LOWER TEMPERATURE USE

WWW.SOLIDSEALING.COM

| | | | | | | | | | |
|--|-------|------------|-------------|----------------------------|-----------|----|-------------------------------------|-------------------------|--|
| PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED. | | | | THIRD ANGLE PROJECTION | | | TITLE: SINGLE ENDED FLOATING BNC | | |
| REV. | APP'D | DATE | SCALE 5:4 | DIMENSIONS IN INCHES [mm] | DRAWN | MH | 09/19/2006 | PART NO. FA14760 REV. A | |
| A2 | JS | 09/27/2012 | COBN0034-21 | | ENG APPR. | MH | 10/27/2006 | | |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.