

| PART NO. | AIR SIDE PLUG | |
|----------|---------------|--|
| FA14786 | МО | |
| KT14786 | YES | |

| RATINGS | | | |
|------------------------------|-----------------|--|--|
| VOLTAGE: | 10KV DC | | |
| CURRENT: | 8.2 AMPS | | |
| PRESSURE: | 120 PSIG @ 20°C | | |
| TEMPERATURE WITHOUT PLUG: | -269°C TO 450°C | | |
| TEMPERATURE WITH PLUG: | -55°C TO 85°C | | |

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

| FERMISSION OF SOLID SEALING TECHNOLOGY IS FROMBITED. | | | | | |
|--|-------|------------|--------------|---------------|--|
| REV. | APP'D | DATE | SCALE 1.5:1 | DIMENSIONS IN | |
| А3 | JS | 10/22/2012 | CO\$10010-01 | INCHES [mm] | |

THIRD ANGLE PROJECTION

DRAWN MH 9/21/2006
ENG APPR. MH 10/27/2006

TITLE:

10KV EXPOSED SHV

PART NO. FA14786 REV. A





DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.