

PART NO.	T/C TYPE	CONDUCTOR MATERIAL
FA14918	R/S	PLATINUM / RHODIUM*
FA14918-02	T	COPPER / CONSTANTAN

RATINGS	
PRESSURE:	1250 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

\*TYPE R/S USES COMPENSATING WIRE  
 MAXIMUM JUNCTION TEMPRATURE 250°C

[WWW.SOLIDSEALING.COM](http://WWW.SOLIDSEALING.COM)




**SOLID SEALING TECHNOLOGY, INC.**

SALES DWG NO. FA14918SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

ONE PAIR T/C LOOP STYLE

PART NO. (SEE TABLE) REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	09/01/2006
A2	JS	05/24/2013	MPC10027-2ST		ENG APPR.	MH	09/01/2006

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**