


PART NO.	AIR SIDE PLUG
FA14920	NO
KT14920	YES

RATINGS	
VOLTAGE:	5KV DC
CURRENT:	8.2 AMPS
PRESSURE:	1500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-65°C TO 165°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

THREE 5KV RECESSED SHV

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	9/21/2006
A2	JS	10/22/2012	COSS0012-02		ENG APPR.	MH	10/27/2006

PART NO. FA14920 REV. A

SALES DWG NO. FA14920SL REV. A2