



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUGS
FA14928	COPPER	30 AMPS	55 AMPS
FA14928-02	MOLYBDENUM	28 AMPS	28 AMPS
FA14928-03	NICKEL	16.5 AMPS	16.5 AMPS
FA14928-04	304 STN STL	3.6 AMPS	3.6 AMPS

RATINGS		
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	20KV DC	10KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
PRESSURE:	0 PSIG @ 20°C*	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 125°C	-25°C TO 205°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG
AN OVERPRESSURE RING IS REQUIRED.

MATES WITH POWERPLUG FP10883 & FP10883-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				<div>THIRD ANGLE PROJECTION</div> 		TITLE EIGHT 20 KV FEEDTHROUGHS			 <div>SOLID SEALING TECHNOLOGY</div>	
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	08/29/2006	PART NO. (SEE TABLE) REV. B	WWW.SOLIDSEALING.COM	
B1	JF	01/31/2025	MPST0052-0ST		ENG APPR.	MH	08/29/2006		SALES DWG NO. FA14928SL REV. B1	

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.