

PLUGS SOLD SEPARATELY
 - AIR SIDE W/ SOLDER CONTACTS FP14901
 - AIR SIDE W/CRIMP CONTACTS KT14379

RATINGS	
VOLTAGE:	1 KV DC
CURRENT:	3 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE:	-25°C TO 205°C

*FOR AN INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

LEAK RATE <1 X 10E-10 ATM-CC/SEC (He)

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14948SL REV. A4

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

19 PIN CONNECTOR

PART NO. FA14948 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	03/29/2006
A4	JF	06/22/2016	MPL0101-01SL		ENG APPR.	MH	04/06/2006

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.